

WASTE HANDLER







HYDRAULIC REVERSIBLE FAN



REAR GRILLE GUARD



WASTE HANDLER CONTENTS



ARTICULATION PROTECTION



BOTTOM GUARD



FRONT FRAME & AXLE PROTECTION



CYLINDERS PROTECTION

MAXIMUM POWER

169 kW - 227 hp

MAX OPERATING WEIGHT

19 800 kg

HIGH DUMP BUCKET CAPACITY

 $3.5 \, \mathrm{m}^3$



ADDITIONAL FEATURES



AUTOMATIC GREASING SYSTEM





FLEXIBLE LADDER STEP



SPECIFICATIONS

Machine equipped with MICHELIN tyres 23.5 R 25 XMINE-D2





BUCKET TYPE		DUMP HEIGHT BUCKET
Bucket capacity	m³	3.5
Bucket weight	kg	2500
Bucket width	mm	3000
Dump height at 45° (Bucket retracted/tipped) (▲)	mm	3430/4745
Reach at 45° (Bucket retracted/tipped) (*)	mm	1220/1310
Overall length (Bucket on ground)	mm	8945
Overall height (Bucket retracted/tipped) (■)	mm	6015/6590
Turning radius (at bucket edge)	m	7.35
Breakout force (Bucket retracted)	daN	15500
Static tipping load: (with bucket retracted) 0°	kg	10100
Static tipping load: (with bucket retracted) 40°	kg	8650
Operating weight	kg	19.800

AT YOUR OWN DEALERSHIP

The information contained in this brochure is intended to be a general nature only. The NEW HOLLAND KOBELCO CONSTRUCTION MACHINERY S.p.A. company may at any time and from time to time, for technical or other necessary reasons, modify any of the details or specifications of the product described in this brochure. Illustrations do not necessarily show products in standard conditions. The dimensions, weights and capacities shown herein, as well as any conversion data used, are approximate only and are subject to variations within normal manufactoring techniques.

Published by NEW HOLLAND KOBELCO CONSTRUCTION MACHINERY S.p.A Printed in Italy - LEADER Firenze - Cod. 30 603GB - Printed 04/09

Printed on recycled paper CoC-FSC 000010 CQ Mixed sources









